

## WHAT IS CLAIMED IS:

## 1. A circuit comprising:

5 a plurality of processing blocks on a first substrate; and

an interconnect network comprising a plurality of network nodes arranged in a two-dimensional array on said first substrate, each network node having a plurality of adjacent network nodes and being connected to each adjacent network node by a communication bus that  
10 connects only those two network nodes and processing blocks adjacent to that bus;

each network node comprising:

a plurality of communication ports, each communication port comprising an input port  
15 for receiving digital signals and an output port for transmitting digital signals on a bus connected to that communication port;

a programmable switch that selectively connects one of said input ports to one of said output ports in response to connection information stored in a memory in that network node,  
20 wherein;

each processing block is connected to one of said communication buses and sends and/or receives data on that bus, each processing block performing a predetermined processing function, said processing block being located within said two-dimensional array of network nodes.  
25

2. The circuit of Claim 1 wherein said connection information is stored in said network nodes prior to said processing blocks commencing said processing functions.

3. The circuit of Claim 1 further comprising a programming bus for transmitting said  
30 connection information to each of said network nodes.

4. The circuit of Claim 1 wherein each of said buses is a serial bus.

5. The circuit of Claim 1 wherein said two dimensional array comprises a rectangular  
5 array in which said network nodes are organized as a plurality of rows and columns.

6. The circuit of Claim 1 further comprising:

10 a second substrate that overlies said first substrate, said second substrate comprising an  
interconnect network comprising a plurality of network nodes arranged in a two-dimensional  
array on said second substrate, each network node having a plurality of adjacent network nodes  
and being connected to each adjacent network node by a communication bus that connects only  
those two network nodes;

15 each network node comprising:

a plurality of communication ports, each communication port comprising an input port  
for receiving digital signals and an output port for transmitting digital signals on a bus connected  
to that communication port;

20 a programmable switch that selectively connects one of said input ports to one of said  
output ports in response to connection information stored in a memory in that network node,

25 wherein at least one of said network nodes on said second substrate is connected to a  
corresponding network node on said first substrate by a bus that connects only those two network  
nodes.

7. The circuit of Claim 1 wherein one of said processing blocks specifies said connection  
information that is stored in each of said network nodes.

30

8. The circuit of Claim 7 wherein said one of said processing blocks also comprises an interface for receiving said connection information from a source external to said circuit.

5 9. The circuit of Claim 1 wherein one of said processing blocks is a spare processing block that is capable of performing processing functions that are normally performed by a second one of said processing blocks if said second one of said processing blocks is defective.